

Advantage Sealing Systems

"Finest Asphalt Emulsion Made"

SAFETY DATA SHEET

Prepared to U.S. OSHA, CMA, ANSI, Canadian WHMIS Standards, Australian WorkSafe, Japanese Industrial Standard JIS Z 7250:2000, and European Union standards

1. PRODUCT IDENTIFICATION

TRADE NAME (AS LABELED):

HPS / APS

MANUFACTURER'S NAME:

ADVANTAGE SEALING SYSTEMS

ADDRESS:

14388 Santa Ana Ave, Fontana CA 92337

BUSINESS PHONE:

(909) 823-1811

EMERGENCY PHONE:

(800) 424-9300 (CHEMTREC)

DATE ISSUED:

June 20, 2022

REVISION DATE:

June 20, 2022

2. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW:

Product Description: Asphalt is a hydrocarbon mixture combination of hydrocarbon compound containing relatively high proportion of compounds with high carbon to hydrogen ratio, sometimes oxidized and mixed with polymer additive to meet customer's specifications. **Health Hazards:** Exposure to liquid or vapor may cause eye irritation. Prolonged or repeated exposure to skin can cause irritation and/or dermatitis. Exposure to high vapor concentrations can cause respiratory irritation. If swallowed this product may get sucked into lungs (aspirated) and cause lung damage or even death. **Flammability Hazards:** This product is a Flammable Liquid. **Reactivity Hazards:** Hot product will cause explosion if it comes in contact with water. **Environmental Hazards:** This product may be harmful to aquatic life if released into the environment. **Emergency Considerations:** Emergency responders must wear the proper personal protective equipment suitable for the situation to which they are responding.

EU LABELING AND CLASSIFICATION: This product meets the definition of a hazardous substance or preparation according to EU Regulations (EC) No 1272/2008.

INDEX NUMBER:

EC# 232-490-9 This substance is not classified in the Annex I of Directive 67/548/EEC

EC# 265-196-4 This substance is not classified in the Annex I of Directive 67/548/EEC

EC# 231-977-3 Is listed in Annex I, Index# 016-001-00-

4 GHS CLASSIFICATIONS:

Flammable Gas Category 1

Acute Toxicity Category

2 SIGNAL WORD:



Danger

HAZARD STATEMENT:

H220 Extremely Flammable gas

H330 Fatal if inhaled

H400 Very Toxic to aquatic life

PREVENTION STATEMENT:

P260 Avoid breathing

dust/fume/gas/mist/vapors/spray P271 Use in well ventilated area.

P281 Use personal protective equipment as required

14388 Santa Ana Ave. Fontana, CA 92337

Phone: 909-823-1811 | Email: sales@advantagesealing.com

HEALTH HAZARDS OR RISKS FROM EXPOSURE:

HEALTH AND SAFETY ALERT:

Hydrogen Sulfide (H₂S) is an extremely flammable, highly toxic gas, which can be emitted from heated asphalt and may accumulate in storage tanks and bulk transportation compartments. At low concentration, H₂S is irritating to eyes and throat, and at high concentration can cause rapid unconsciousness and death. Use proper ventilation or work upwind from the source of fumes and vapor.

Potential Health Effects: Acute (Short Term):

This product, if heated, may release asphalt fumes that may cause irritation to the throat, nose and skin irritation. If inhaled, the fumes may cause nausea, headache, or dizziness. Prolonged and repeated contact with cold asphalt may cause dermatitis and other skin problems, while contact with hot product will cause thermal burns. If ingested, the product may cause internal organ irritation and upset that may cause possible nausea, vomiting, and diarrhea. Hot asphalt droplets or particles can cause eye burns or irritation. A splash in the eye of hot asphalt can cause serious eye injury.

Chronic (Long Term):

Prolonged and repeated contact with asphalt may cause dermatitis and other skin problems. Studies show that asphalt is possibly carcinogenic to humans with limited evidence in humans in the absence of sufficient evidence in experimental animals. However, this product contains low levels of polynuclear aromatics, which may cause skin lesions and skin cancer.

Medical Condition Generally Aggravated by Exposure:

Medical conditions that show or have the same symptoms and effects as those outlined under health hazard information section or an individual that has a history of chronic skin or respiratory conditions can be aggravated by exposure to this product.

Possible Route(s) of Entry: Inhalation of dust and fumes, skin, eye, and ingestion.

3. COMPOSITION and INFORMATION ON INGREDIENTS

Asphalt is a hydrocarbon mixture combination of hydrocarbon compounds containing relatively high proportion of compounds with high carbon to hydrogen ratio, sometimes oxidized and mixed with polymer additive to meet customer's specifications.

Common Name – Asphalt **Chemical Name** – Petroleum Asphalt

CAS No. – 8052-42-4 **Wt. %** - ~50-100

NOTE: ALL WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2004 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR, EU Directives and the Japanese Industrial Standard JIS Z 7250: 2000.

4. FIRST AID MEASURES

Inhalation: Remove individual from exposure. If problems persist, administer artificial respirator and seek medical attention.

Skin Contact: If hot product strikes skin, drench area with water to assist cooling. DO NOT try to remove product from burn after it has cooled. Seek medical attention. Medical personnel can remove cooled products with petroleum jelly. If cooled product contact with skin, wash area with hot soapy water.

Eye Contact: If asphalt gets into the eyes, remove any contact lenses at once and irrigate immediately for 15 minutes. Occasionally lifting upper and lower lids.

Ingestion: DO NOT induce vomiting. In general, no treatment is necessary, unless large quantities are ingested. However, seek medical attention.

5. FIRE-FIGHTING MEASURES

FLASH POINT: >525° F

14388 Santa Ana Ave. Fontana, CA 92337

Phone: 909-823-1811 | Email: sales@advantagesealing.com

AUTOIGNITION TEMPERATURE: Not Established

FLAMMABLE LIMITS (in air by volume, %): Lower NA Upper NA

FIRE EXTINGUISHING MATERIALS: Limited water spray, carbon dioxide, foam, dry chemical, halon, other "B" type


UNUSUAL FIRE AND EXPLOSION HAZARDS: Hot product may ignite flammable material on flash. DO NOT heat above flash point.

Explosion Sensitivity to Mechanical Impact: Not Sensitive

Explosion Sensitivity to Static Discharge: Not Sensitive

SPECIAL FIRE-FIGHTING PROCEDURES: Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

NFPA RATING:



Scale: 0 = Minimal 1 = Slight 2 = Moderate

3 = Serious 4 = Severe * = Chronic hazard

6. ACCIDENTAL RELEASE MEASURES

It is user's responsibility to report any accidental release as required by applicable federal, state, and/or local agencies.

Procedure:

Call 911. Keep liquid out of watercourse and sewers. Isolate hazard area and deny entry to non-emergency personnel. Eliminate source of ignition, dike spills.

Other Information:

Absorbent Material: Sand and soil.

Incompatible Material: Water, avoid contact with water.

7. HANDLING and STORAGE

Handling and Storage:

DO NOT store heated material above its flash point and DO NOT load material to container that has water. In general, protect against physical damage. Outside or detached storage is preferred. Keep containers separated from strong oxidizer materials. Asphalt may contain hydrogen sulfide and sulfur dioxide; therefore, it is recommended to wear appropriate respiratory protection when first opening containers.

8. EXPOSURE CONTROLS - PERSONAL PROTECTION

General Work Hygienic Practices:

Always wear recommended PPE and wash hands after handling material. Avoid any unnecessary exposure to the material. Shower after exposure and wash work clothes when contaminated. Safety showers and eye wash stations should be available.

Ventilation:

Provide sufficient local and/or general exhaust ventilation. In outdoor applications where material is heated, keep kettle downwind of workers.

14388 Santa Ana Ave. Fontana, CA 92337

Phone: 909-823-1811 | Email: sales@advantagesealing.com

Personal Protective Equipment

Respiratory protection:

Respiratory protection is not required during normal use. However, when first opening tank trucks, railcars, or other containers, it is recommended to wear appropriate NIOSH approved respiratory protection. Appropriate NIOSH approved respiratory protection must be worn if material is heated and/or generate asphalt fumes and/or hydrogen sulfide above the OSHA and ACGIH recommended limits. Use respiratory protection in accordance with your company's respiratory program.

Skin protection:

At least workers have to wear loose-fitting, long-sleeved shirt and long pants. When encounter the hot material, heat insulated, leather, or lined neoprene coated gloves should be worn.

Eye protection:

Safety glasses or chemical goggles may be required.

Hazardous Ingredients:

| Ingredients | OSHA PEL | ACGIH TLV |
|------------------|--|---|
| Asphalt | 5 mg/m ³ (respirable) 15 mg/m ³ (total) | 0.5 mg/m ³ (as benzene-extractable inhalable particulate) |
| Hydrogen Sulfide | 20 ppm ceiling | 10 ppm 15 ppm STEL |

9. PHYSICAL and CHEMICAL PROPERTIES

| | | | |
|----------------------|--|-------------------|-----------------------|
| Appearance and Odor: | Brown to black heavy liquid or solid with petroleum odor | | |
| Molecular Weight: | 800 to 2000 | | |
| Boiling Point: | Above 700F | | |
| Melting Point: | 140F to 250F | | |
| Vapor Pressure: | N/A | | |
| Vapor Density: | N/A (air=1) | | |
| Specific Gravity: | >1 (water=1) | | |
| Solubility in Water: | N/A | Evaporation Rate: | N/A (butyl acetate=1) |

10. STABILITY and REACTIVITY

Stability: Stable

Reactivity: Hot product will cause explosion if it comes in contact with water. Avoid contact with strong oxidizer.

Hazardous Polymerization: Will not occur

11. TOXICOLOGICAL INFORMATION

| | | | | |
|-------------------|-------|------|-----|------|
| Carcinogenicity: | | | | |
| Ingredients | ACGIH | IARC | NTP | OSHA |
| Petroleum Asphalt | A4 | 3 | No | No |
| Hydrogen Sulfide | No | No | No | No |

A4 = Not Classifiable as Human Carcinogen
3 = Not Classifiable

| | | | |
|-------------------|------------------|--------------------|-----------------------------------|
| Ingredients | LD50 Oral (g/kg) | LD50 Dermal (g/kg) | LC50 Inhalation (ppm) |
| Petroleum Asphalt | Not Available | Not Available | Not Available |
| Hydrogen Sulfide | Not Available | Not Available | 444 (4hr: rat) 634 (1hr: mice) |

14388 Santa Ana Ave. Fontana, CA 92337

Phone: 909-823-1811 | Email: sales@advantagesealing.com

12. ECOLOGICAL INFORMATION

Asphalt is not toxic to animals, plants, or fish

13. DISPOSAL CONSIDERATION

In general asphalt is a non-RCRA hazardous waste. Users must dispose of the material in accordance with all applicable federal, state, and local regulations.

14. TRANSPORT ATION

Product in solid state is not regulated. The following information is for products shipped as bulk liquid.

| | |
|--|--|
| DOT Shipping Name: | Elevated temperature, liquid, n.o.s. |
| Hazard Class: | 9 |
| UN No: | UN 3257 |
| Packing Group: | III |
| Labeling: | 9 |
| Hazardous Material Shipping Description: | Elevated temperature, liquid, no's., 9. UN3257, PG III |

15. Regulatory Information

SARA Title III:

This product is reportable under SARA Title III, Sections 311 and 312 as a hazardous substance.

| | | |
|--------------------|-----------------|-----|
| Hazard Categories: | Acute Health: | Yes |
| | Chronic Health: | Yes |
| | Pressure: | No |
| | Fire: | No |
| | Reactive: | No |

Components listed under 40 CFR 372.65:

This product does not contain a chemical identified as toxic by EPA under 40 CFR Part 372 and is not subject to the reporting requirements of this section.

California Proposition 65:

Warning - This product contains chemicals in trace quantities that are known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA (Toxic Substance Control Act):

Asphalt is listed in the TSCA inventory.

16. OTHER INFORMATION

Prepared By : Advantage Sealing Systems, Inc.

Last Revision Date : 1/11/2024

Disclaimer/Statement of Liability : This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to verify the suitability and completeness of such information for particular use. Advantage Sealing does not accept liability for any loss or damage that may occur from the use of this information.