



ASSI- HPS
Product Data Sheet

Description

HPS is a strong, precisely engineered non-tracking polymer tack coat designed as an adhesive interlayer between surfaces. It helps rejuvenate the existing substrate by restoring light ends while creating a clean, effective bond with the new surface layer. Formulated to cure upon immediate contact, HPS allows treated pavements to be driven on and paved over right away, eliminating the need for expensive construction delays, road closures, or post-construction cleanup.

SPECIFICATIONS: Meets ASSI internal testing requirements.

SURFACE PREPARATION: Surfaces should be dry and as clean as possible before applying. Remove dirt, dust, and rocks before applying coating.

APPLICATION: Application rates vary depending on the existing surface, so please consult applicable agency specifications to determine required application rate.

COVERAGE RATE: Rates are between 0.10 and 0.15 gallons per square yard.

CLEAN-UP: Refer to SDS for further information.

HIGHLIGHTS:

- **No Pickup**
- **SBS and Tire Rubber modified chemistry**
- **Very high interlay adhesion**
- **Increase tear strength of fabric and layers**
- **Cure on contact-open to traffic immediately!**
- **Low viscosity for desirable spray application.**

WARNING! HARMFUL OR FATAL IF SWALLOWED. FOR EXTERIOR USE ONLY. KEEP OUT OF REACH OF CHILDREN.

Typical Properties:

PROPERTY	METHOD	RESULT
Penetration, 25C	ASTM D5, AASHTO T49	6-9
Flash Point, COC, C	ASTM D92, AASHTO T48	230 min.
Softening Point, C	ASTM D36, AASHTO T53	20-100 secs.
Solubility of TCE, %	AASHTO T44, ASTM D2043	97.5 min.
Viscosity, 165C, Pa.s	AASHTO T316, ASTM D4402	0.3 max

Application Temperature recommended: 350F-375F

Set up time: upon contact depending on conditions.

WARRANTY AND DISCLAIMER: This product is believed to be of good quality and to be in accordance with the specifications set forth herein. If the product proves to be defective, it shall be replaced at the cost of Advantage. Such replacement is and shall be the only liability of Advantage. Advantage is not liable for product failure where poor drainage and ponding water exist. Advantage shall not be responsible to the consumer or any person for labor costs of any kind or any other costs or damages associated with the product or its installation, application or reapplication or any damages resulting therefrom. This warranty is exclusive and there are no other warranties either expressed or implied, including warranties of fitness or merchantability. No other written or oral representation by any person, entity, dealer, installer or representative of Advantage shall have any force or effect. For additional warranty and disclaimer information, contact the Advantage corporate office at www.Advantagesealing.com.